

Missouri Department of Transportation
Patrick K. McKenna, Director

573.751.2551
Fax: 573.751.6555
1.888.ASK MODOT (275.6636)

ADDENDUM 002
Transit Vehicles - Lowered Floor Mobility Vehicle
Request for Bid 3-160824TVD

Bidders should acknowledge receipt of Addendum 002 (TWO) by **signing and including it** with the original bid. The due date for receipt of bids is extended to **September 8, 2016 @ 12:30pm** by this Addendum 002. Accordingly, the following clarifications are believed to be of general interest to all potential bidders. All other terms and conditions remain unchanged and in full force.

Name and Title of Signer (Print or type)	Name and Title of Department Authority Name: Tom Veasman Title: Sr. General Services Specialist
Contractor/Bidder Signature	Department of Transportation 
(Signature of person authorized to sign)	(Authorizing Signature)
Date Signed:	Date Signed: 8-23-16

3-160824TVD – Transit Vehicles – Lowered Floor Mobility Vehicle

CHANGES TO SPECIFICATIONS:

Remove (1st Addendum Language):

Back-Up Warning Device: Shall be equipped with an audible warning device in compliance with SAEJ994b that is activated when the vehicle transmission is engaged in reverse and continues as the vehicle is being backed up. This should be located behind the rear axle of the vehicle and all wires must be enclosed and secured. An audible adjustable signal, with a minimum range of 87 dBA, shall be included.

Replace with (2nd Addendum Language):

Back-Up Warning Device: Shall be equipped with an audible warning device in compliance with SAEJ994b that is activated when the vehicle transmission is engaged in reverse and continues as the vehicle is being backed up. This should be located behind the rear axle of the vehicle and all wires must be enclosed and secured. An audible self-adjustable signal, with a minimum range of 87 dBA, shall be included.

Remove (Original Specification):

ALTERNATOR:

12 Volt, 155 Amps, minimum or OEM maximum.

Replace with:

ALTERNATOR:

OEM standard.

Remove (Original Specification):

OVERALL HEIGHT:

Maximum 75 inches.

Replace with:

OVERALL HEIGHT:

Minimum 75 inches.

Remove (Original Specification):

WHEELS AND TIRES:

Tire size must be compatible with each vehicle and must meet 6,600 lb. GVWR minimum.

- Tires shall be steel-belted radial all season type tires.
- Wheels shall be made of steel.
- Shall have full Wheel covers.
- Shall have a tire sealant and inflator kit included.
- Shall have a mounted spare tire.

Replace with:

WHEELS AND TIRES:

Tire size must be compatible with each vehicle and must meet 6,600 lb. GVWR minimum.

- Tires shall be steel-belted radial all season type tires.
- Wheels shall be made of steel.
- Shall have full Wheel covers.
- Shall have a tire sealant and inflator kit included.
- Shall have spare tire *shipped loose*.

Remove (Original Specification):

Vendor is responsible for coordinating all warranty work of ALL equipment on the vehicle during the warranty period. All repairs need to minimize the number of days the unit is out of service.